

WWW.SOMOVALV.COM


MOLLE E VALVOLE NAVALI ED INDUSTRIALI
di Florio Maurizio & C.

VIA MILANO 162 R\R - 16126 GENOVA

Part. IVA 03138200104

Tel. 010411226 Fax 010411267



E-mail: INFO@SOMOVALV.IT







DIN

DIN

Deutsches Institut für Normung

ITEM	GLOBE	ANGLE	GLOBE	ANGLE	OVERBOARD
CLASS	PN16	PN16	PN16	PN16	PN16
SERIES	2622	3622	2022	3022	3522
TYPE					
SIZE	15 - 100	15 - 100	15 - 400	15 - 400	20 - 300

ITEM	GATE		FIRE HOSE		LIFT CHECK
CLASS	PN16	PN16	PN16	PN16	PN16
SERIES	1622	1022	2222	3222	2322
TYPE					
SIZE	15 - 500	40 - 300	40 - 65	40 - 65	15 - 300


ITEM	STRAINER	STORM	PRESSURE REDUCER
CLASS	PN16	PN10/16	PN16/40
SERIES	0522	4322	0322
TYPE			
SIZE	15 - 300	50 - 150	15 - 150


STANDARD FEATURES


Globes and Angles: Shut-Off and
Screw-Down Non-Return
Gates: Rising and Non-Rising Stem
Trims: Brass and Chrome13

UPON REQUEST

Globes and Angles: Spring-Loaded
and Bellows Seal
Gates: Flex and Split Wedges
Special Trims
Alternate Flange Drillings

ITEM	GLOBE	ANGLE	GATE		
CLASS	PN16	PN16	PN10	PN16*	PN16
SERIES	2002	3002	1001	1032*	1202
TYPE					
SIZE	15 - 400	15 - 400	40 - 600	40 - 300	40 - 300

ITEM	SAFETY		BUTTERFLY		
CLASS	PN16	PN16	PN10 / 16	PN10 / 16	PN10 / 16
SERIES	7012	7212	5002 - LEVER	5002 - GEAR	5232*
TYPE					
SIZE	15 - 150	25 - 150	40 - 200	150 - 600	50 - 600

ITEM	STRAINER	LIFT CHECK
CLASS	PN16	PN16
SERIES	0502	2302
TYPE		
SIZE	15 - 300	15 - 300

STANDARD FEATURES

Globes and Angles: Shut-Off and
Screw-Down Non-Return

Gates: Rising and Non-Rising Stem

Trims: Brass and Chrome13

UPON REQUEST



Globes and Angles: Spring-Loaded
and Bellows Seal





Gates: Flex and Split Wedges


Special Trims

Alternate Flange Drillings

*Only Available in Ductile Iron

ITEM	GLOBE	ANGLE	GLOBE	GATE	
CLASS	PN16 / 40	PN16 / 40	PN100	PN16	PN16 / 25 / 40
SERIES	2015	3015	2017	1012	1212
TYPE					
SIZE	15 - 400	15 - 400	15 - 150	40 - 600	40 - 600

ITEM	SAFETY		STORM		OVERBOARD
CLASS	PN16 / 40	PN16 / 40	PN10	PN10	PN10 / 16
SERIES	7015	7215	4211	4311	3512
TYPE					
SIZE	15 - 150	25 - 150	50 - 150	50 - 150	20 - 300

ITEM	STRAINER	LIFT CHECK	BUTTERFLY
CLASS	PN16/40	PN16/40	PN10/16
SERIES	0512	2312	5212
TYPE			
SIZE	15 - 300	15 - 300	50 - 600

STANDARD FEATURES

Globes and Angles: Shut-Off and Screw-Down Non-Retu

Gates: Rising and Non-Rising Stem

Trims: Brass and Chrome13



UPON REQUEST



Globes and Angles: Spring-Loaded and Bellows Seal


Gates: Flex and Split Wedges

Special Trims

Alternate Flange Drillings

ITEM	WAFER CHECK	DUO CHECK	DIAPHRAGM	VENT CHECK	QUICK CLOSING
CLASS	AS REQUESTED				
FIG NO	4002	4102	8001	4501	1602
TYPE					
SIZE	40 - 600	40 - 600	15 - 500	50 - 300	3/8" - 4"

ITEM	SOUNDING COCK	BALL	NEEDLE	EXPANSION JOINTS	
CLASS	AS REQUESTED				
FIG NO	9402	6202	0001	RUBBER	METAL
TYPE					
SIZE	1-1/2", 2"	1/4" - 4"	1/4" - 1"	40 - 600	40 - 600

ITEM	STRAUB	DRESSER
CLASS	AS REQUESTED	
FIG NO	"STRAUB"	"DRESSER"
TYPE		
SIZE	40 - 600	40 - 600

THE ABOVE ITEMS ARE AVAILABLE
IN VARIOUS MATERIALS AND TO ANSI,
DIN, JIS STANDARDS, WHERE
APPLICABLE.


SIZE		PN 6	PN 10	PN 16	PN 25	PN 40
10 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLE	75 50 4 X 11	90 60 4 X 14	90 60 4 X 14	90 60 4 X 14	90 70 4 X 14
15 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLES	80 55 4 X 11	95 65 4 X 14	95 65 4 X 14	95 65 4 X 14	95 65 4 X 14
20 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLES	90 65 4 X 11	105 75 4 X 14	105 75 4 X 14	105 75 4 X 14	105 75 4 X 14
25 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLES	100 75 4 X 11	115 85 4 X 14	115 85 4 X 14	115 85 4 X 14	115 85 4 X 14
32 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLES	120 90 4 X 14	140 100 4 X 18	140 100 4 X 18	140 100 4 X 18	140 100 4 X 18
40 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLES	130 100 4 X 14	150 110 4 X 18	150 110 4 X 18	150 110 4 X 18	150 110 4 X 18
50 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLES	140 110 4 X 14	165 125 4 X 18	165 125 8 X 18	165 125 8 X 18	165 125 8 X 18
65 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLES	160 130 4 X 14	185 145 4 X 18	185 145 4 X 18	185 145 4 X 18	185 145 4 X 18
80 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLES	190 150 4 X 18	200 160 8 X 18	200 160 8 X 18	200 160 8 X 18	200 160 8 X 18
100 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLES	210 170 8 X 18	220 180 8 X 18	220 180 8 X 18	235 190 8 X 22	235 190 8 X 22
125 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLES	240 200 8 X 18	250 210 8 X 18	250 210 8 X 18	270 220 8 X 26	270 220 8 X 26
150 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLES	265 225 8 X 18	285 240 8 X 22	285 240 8 X 22	300 250 8 X 26	300 250 8 X 26
175 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLES		315 270 8 X 22	315 270 8 X 22	330 280 12 X 26	350 295 12 X 30
200 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLES	320 280 8 X 18	340 295 8 X 22	340 295 12 X 22	360 310 12 X 26	375 320 12 X 30
250 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLES	375 335 12 X 18	395 350 12 X 22	405 355 12 X 26	425 370 12 X 30	450 385 12 X 33
300 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLES	440 395 12 X 22	445 400 12 X 22	460 410 12 X 26	485 430 16 X 30	515 450 16 X 33
350 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLES	490 445 12 X 22	505 460 16 X 22	520 470 16 X 26	555 490 16 X 33	580 510 16 X 36
400 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLES	540 495 16 X 22	565 515 16 X 26	580 525 16 X 30	620 550 16 X 36	660 585 16 X 39
500 MM	FLANGE DIAMETER BOLT CIRCLE NUMBER & SIZE OF HOLES	645 600 20 X 22	670 620 20 X 26	715 650 20 X 33	730 660 20 X 36	755 670 20 X 42

MATERIAL	MATERIAL NO	DIN DESCRIPTION	DIN MATERIAL STANDARD	ASTM DESCRIPTION
CAST IRON	0.6020	GG - 20	DIN 1691	A 48-76 GRADE 30 B
	0.6025	GG - 25	DIN 1691	A 48-76 GRADE 40 B
	0.6030	GG - 30	DIN 1691	A 48-76 GRADE 45 B
NODULAR IRON	0.7040	GGG-40	DIN 1693	A 536 80 GRADE 60-40-18
	0.7043	GGG-40.3	DIN 1693	
	0.7050	GGG-50	DIN 1693	A 536 80
STEEL	1.0038	RST 37-2	DIN 17100	A675 60
	1.0040	USt 42-2		A675 GRADE 60
	1.0065	USt 37-1	DIN 17100	A 675 GRADE 50
	1.0402	C 22	DIN 17200	A 107 GRADE 1020
	1.0460	C 22.8	DIN 17243	
	1.0619	GS-C 25	DIN 17245	A 216 GRADE WCB
	1.4009	X8 Cr 14	DIN 17145	
	1.4016	X 8 Cr 17	DIN 17440	A 276 TYPE 430
STAINLESS STEEL	1.4021	X 20 CR 13	DIN 17440	A 276 TYPE 420
	1.4301	X 5 Cr Ni 189	DIN 17440	A 276 TYPE 304
	1.4401	X 5 C r Ni Mo 18 10	DIN 17440	A 276 TYPE 316
	1.4408	G X 6 Cr Ni Mo 18 10	DIN E 17445	A 351 GRADE CF 8M
	1.4502	X 8 Cr Ti 18	DIN 17440	
	1.4539	X 2 Ni CVr Mo CU 25 20 5		B 625 UNS N 08904
	1.4541	X 10 Ni Ti 189	DIN 17440	A 276 TYPE 321
	1.4552	G-X7 Cr Ni Nb	DIN 17445	A 351 GRADE CF 8C
	1.4571	X 10 Cr Ni Mo Ti 18 10	DIN 17440	A 276 TYPE 316 Ti
	1.4581	G X 5 Cr Ni Mo Nb 18 10	DIN 17445	
COPPER ALLOY	2.0380.10	Cu Zn 39 Pb 2 F 37	DIN 17672	B 124 C 37700
	2.0401	Cu Zn 39 Pb 3	DIN 17660	B 1679 C 36 000
	2.0401.08	Cu Zn 39 Pb 3 P	DIN 17672	B 124 C 37700
	2.0406	C u Zn 41 Pb 62	DIN 17672	B 124 C 37700
	2.0490.31	Cu Zn 31 S 1 F 50	DIN 17672	
	2.0540.09	Cu Zn 35 Ni F 35	DIN 17672	B 283 ALLOY A
	2.1096.01	G-Cu Sn 5 Zn Pb	DIN 1705	ASTM B 145 GRADE 4 A

<u>Page</u>	<u>Series</u>	<u>Type</u>	<u>Material</u>	<u>Pressure</u>
DIN Gates				
3	1001	NRS	Cast Iron	PN10
4	1011 - 1012	NRS	Cast Steel	PN16
5	1022	NRS	Bronze	PN16
6	1032	NRS	Ductile Iron	PN16
7	1202	NRS	Cast Iron	PN16
8	1302	OS&Y	Cast Iron	PN16
9	1311-1312-1313	OS&Y	Cast Steel	PN10-16-25
10	1422 - 1622	NRS	Bronze	PN16
DIN Globes				
11	2002 - 2102	Regular & SDNR	Cast Iron	PN16
12	2012 - 2112	Regular & SDNR	Cast Steel	PN16
13	2015 - 2115	Regular & SDNR	Cast Steel	PN40
14	2017 - 2117	Regular & SDNR	Cast Steel	PN100
15	2018 - 2118	Regular & SDNR	Cast Steel	PN160
16	2022 - 2122	Regular & SDNR	Bronze	PN16
17	2032 - 2132	Regular & SDNR	Ductile Iron	PN16
DIN Angles				
18	3002 - 3102	Regular & SDNR	Cast Iron	PN16
19	3012 - 3112	Regular & SDNR	Cast Steel	PN16
20	3015 - 3115	Regular & SDNR	Cast Steel	PN40
21	3022 - 3122	Regular & SDNR	Bronze	PN16
22	3032 - 3132	Regular & SDNR	Ductile Iron	PN16
DIN Globes & Angles (others)				
23	2222 - 3222	Hose	Bronze	PN16
24	2312 - 3312	Overboard	Cast Steel	PN16
25	2415 - 3415	Quick-Closing	Cast Steel	PN40
26	2522 - 3522	Union Bonnet	Bronze	PN16
27	2722 - 3722	Regular	Bronze	PN16
DIN Checks				
28	4012	Wafer Swing	Cast Steel	PN16
29	4022 - 4052	Wafer Swing	Bronze - Stainless Steel	PN16
30	4101 - 4111	Duo-Check	Various	PN16

<u>Page</u>	<u>Series</u>	<u>Type</u>	<u>Material</u>	<u>Pressure</u>
DIN Checks (continued)				
31	4211 - 4311	Storm	Cast Steel	PN10
31 bis		Vertical & Angle Pattern		
32	4402	Swing	Cast Iron	PN16
33	4412	Swing	Cast Steel	PN16
34	4602	Lift Globe	Cast Iron	PN16
35	4615	Lift Globe	Cast Steel	PN40
34	4702	Lift Angle	Cast Iron	PN16
35	4715	Lift Angle	Cast Steel	PN40
36	4822 - 4865	Disc	Various	PN10
37	4901	Vent	Cast Iron	PN10
Miscellaneous				
38	62	Ball Valves	Various	PN16 - PN40
39	80	Pressure Reducing	Bronze	PN30
40	8202 - 8215	Y-Strainers	Various	PN16 - PN40
41	84	Needle	Stainless Steel	PN500
42	XRD10	Expansion Bellow	Rubber	PN10
DIN Butterfly				
43 - 44	Material Selection Guide			
45 - 46	50 - 52 - 55	Wafer - Lug - Flanged	Various	PN10 - PN16
47 - 48	53 - 54 - 56	Mono & Flanged	Various	PN10 - PN16
49	58	Teflon Lined	Various	PN10 - PN16
50	Actuators	Lever & Worm Gear		
Flanges				
51-52	DIN 2573 DIN 2576 DIN 2527	Slip-On	Various	PN6 - PN40
53	DIN 2633 DIN 2635	Weld-Neck	Various	PN16 - PN40
54	DIN 86029 DIN 86030	Raised Face	Various	PN10 - PN16
Conversion Tables				
55	Linear			
56	Pressure			
57	Temperature			

Series 1001 ... NRS




Face to Face according to DIN 3202-F4
Flanges as per DIN 2501 - PN10

Part Nr.	Material	Code	Size	Nom. Pressure	Hydraulic Inspection	
1 - Body	Cast Iron	GG25	DN	PN	Body	Seat
2 - Seat	Brass	UNI 5035	40 to 250	10	16	10
3 - Disc	Brass	UNI 5035	300 to 600	6	10	6
4 - Stem	Brass	UNI 5035				

Size	L	D	C	No.	h	t	H	D2	Kg
40	140	150	110	4	18	16	230	160	11
50	150	165	125	4	18	18	245	160	12
65	170	185	145	4	18	18	290	160	17
80	180	200	160	8	18	20	315	160	18
100	190	220	180	8	18	20	355	200	35
125	200	250	210	8	18	22	415	250	35
150	210	285	240	8	22	22	460	250	46
175	220	315	270	8	22	24	510	250	66
200	230	340	295	8	22	24	545	315	75
250	250	395	350	12	22	26	635	315	110
300	270	445	400	12	22	26	725	400	115
350	290	505	460	16	22	26	830	400	242
400	310	565	515	16	26	26	945	400	285
500	350	670	620	20	26	28	1120	500	410
600	390	780	725	20	30	28	1300	500	573

Series 1011 ... PN10

Series 1012 ... PN16



Face to Face according to DIN 3202-F4


Flanges according to DIN2501-PN10 or 16

Part Nr.	Material	Code
1 - Body	Cast Steel	GSC-25N
2 - Seat	Stainless Steel	AISI 420
3 - Disc	Stainless Steel	AISI 410
4 - Stem	Stainless Steel	AISI 410

Size DN	Nom. Pressure	Hydraulic Inspection	
	PN	Body	Seat
40 to 500	16	25	16
200 to 600	10	16	10

Size	L	DIN PN10						DIN PN16					H	D2	Kg
		D	C	No.	h	t		D	C	No.	h	t			
40	140	Same as DIN PN16						150	110	4	18	16	230	160	11
50	150	Same as DIN PN16						165	125	4	18	18	245	160	12
65	170	Same as DIN PN 16						185	145	4	18	18	290	160	17
80	180	200	160	4	18	20		200	160	8	18	20	315	160	18
100	190	Same as DIN PN 16						220	180	8	18	20	355	200	35
125	200	Same as DIN PN 16						250	210	8	18	22	415	250	35
150	210	Same as DIN PN 16						285	240	8	22	22	460	250	46
175	220	Same as DIN PN16						315	270	8	22	24	510	250	66
200	230	340	295	8	22	24		340	295	12	22	24	545	315	75
250	250	395	350	12	22	26		405	355	12	25	26	635	315	110
300	270	445	400	12	22	28		460	410	12	26	28	725	400	115
350	290	505	460	16	22	30		520	470	16	26	30	830	400	242
400	310	565	515	16	26	32		580	525	16	30	32	945	400	285
500	350	670	620	20	26	34		715	650	20	33	34	1120	500	410
600	390	780	725	20	30	36		-	-	-	-	-	1300	500	573

Series 1022 ... NRS




Face to Face according to DIN 3202-F4

Flanges according to DIN2501-PN16

Part Nr.	Material	Code	Size DN	Nom. Pressure PN	Hydraulic Inspection	
					Body	Seat
1 - Body	Gunmetal Gunmetal Brass	DIN 1705	40 to 175	16	25	16
2 - Disc		DIN 1705				
3 - Stem		DIN 17672	200 to 300	10	16	10

Size	L	D	C	No.	h	t	H	D2	Kg
40	140	150	110	4	18	16	230	160	11
50	150	165	125	4	18	18	245	160	12
65	170	185	145	4	18	18	290	160	17
80	180	200	160	8	18	20	315	160	18
100	190	220	180	8	18	20	355	200	35
125	200	250	210	8	18	22	415	250	35
150	210	285	240	8	22	22	460	250	46
175	220	315	270	8	22	24	510	250	66
200	230	340	295	8	22	24	545	315	75
250	250	395	350	12	22	26	635	315	110
300	270	445	400	12	22	26	725	400	115

Series 1032 ... NRS




Face to Face according to DIN 3202-F4
Flanges as per DIN 2501 - PN16

Part Nr.	Material	Code
1 - Body	Ductile Iron	GGG40
2 - Disc	Ductile Iron with Vulcanized NBR Rubber	GGG40 with NBR
3 - Stem	Stainless Steel	X20Cr13

Size DN	Nom. Pressure	Hydraulic Inspection	
	PN	Body	Seat
40 to 300	16	25	16

Size	L	D	C	No.	h	t	H	D2	Kg
40	140	150	110	4	18	18	140	195	10
50	150	165	125	4	18	18	140	205	11
65	170	185	145	4	18	18	160	230	14
80	180	200	160	8	18	20	160	260	17
100	190	220	180	8	18	20	180	290	21
125	200	250	210	8	18	22	200	345	29
150	210	285	240	8	22	22	200	385	35
200	230	340	295	12	22	24	280	475	53
250	250	405	355	12	26	26	280	565	78
300	270	460	410	12	26	28	325	645	102

Series 1202 ... NRS




Face to Face according to DIN 3202-F5
Flanges according to DIN2501-PN16

Part Nr.	Material	Code	Size		Nom. Pressure		Hydraulic Inspection	
			DN		PN		Body	Seat
1 - Body	Cast Iron	GG25	40 to 300		16		25	16
2 - Stem	Brass	UNI 5035						
3 - Disc	Brass	UNI 5035						
4 - Seat	Brass	UNI 5035						

Size	L	D	C	No.	h	t	D2	H	Kg
40	240	150	110	4	18	18	140	230	16
50	250	165	125	4	18	18	140	265	20
65	270	185	145	4	18	18	160	300	30
80	280	200	160	8	18	20	160	340	36
100	300	220	180	8	18	20	180	370	48
125	325	250	210	8	18	22	200	415	65
150	350	285	240	8	22	22	200	460	81
175	375	315	270	8	22	24	280	510	106
200	400	340	295	12	22	24	280	555	127
250	450	405	355	12	26	26	280	665	183
300	500	460	410	12	26	28	325	730	240

Series 1302 ... OS&Y



Face to Face according to DIN 3202-F5
Flanges according to DIN2501-PN16


Part Nr.		Material	Code	Size		Nom. Pressure		Hydraulic Inspection	
1 - Body		Cast Iron Brass Brass Brass	GG25	DN			PN	Body	Seat
2 - Stem			UNI 5035						
3 - Disc			UNI 5035						
4 - Seat		UNI 5035		40 to 300		16		25	16

Size	L	D	C	No.	h	t	D2	H	Kg
40	240	150	110	4	18	18	140	265	18
50	250	165	125	4	18	18	140	275	22
65	270	185	145	4	18	18	160	335	32
80	280	200	160	8	18	20	160	355	39
100	300	220	180	8	18	20	180	400	51
125	325	250	210	8	18	22	200	495	68
150	350	285	240	8	22	22	200	585	84
175	375	315	270	8	22	24	280	660	109
200	400	340	295	12	22	24	280	700	130
250	450	405	355	12	26	26	280	830	203
300	500	460	410	12	26	28	325	960	259

Series 1311 ... OS&Y - PN10

Series 1312 ... OS&Y - PN16

Series 1313 ... OS&Y - PN25



Face to Face according to DIN 3202-F5


Flanges according to DIN2501-PN10, 16 & 25

Part Nr.	Material	Code
1 - Body	Cast Steel	GSC-25N
2 - Stem	Stainless Steel	AISI 420
3 - Disc	Stainless Steel	AISI 410
4 - Seat	Stainless Steel	AISI 410

Size DN	Nom. Pressure PN	Hydraulic Inspection	
		Body	Seat
40 to 500	25	38	25
40 to 500	16	25	16
40 to 500	10	16	10

Size	L	DIN PN10						DIN PN16						DIN PN25						H	D2	Kg
		D	C	No.	h	t		D	C	No.	h	t		D	C	No.	h	t				
40	240	Same as DIN PN 25						Same as DIN PN 25						150	110	4	18	18		230	160	11
50	250	Same as DIN PN 25						Same as DIN PN 25						165	125	4	18	20		245	160	12
65	270	Same as DIN PN 16						185	145	4	18	18		185	145	8	18	22		290	160	17
80	280	200	160	4	18	22		Same as DIN PN25						200	160	8	18	24		315	160	18
100	300	Same as DIN PN 16						220	180	8	18	20		235	190	8	22	24		355	200	35
125	325	Same as DIN PN 16						250	210	8	18	22		270	220	8	26	26		415	250	35
150	350	Same as DIN PN 16						285	240	8	22	22		300	250	8	26	28		460	250	46
200	400	340	295	8	22	24		340	295	12	22	24		375	320	12	30	34		545	315	75
250	450	395	350	12	22	26		405	355	12	25	26		450	385	12	33	38		635	315	110
300	500	445	400	12	22	26		460	410	12	26	28		515	450	16	33	42		725	400	115
350	550	505	460	16	22	26		520	470	16	26	30		580	510	16	36	46		830	400	242
400	600	565	515	16	26	26		580	525	16	30	32		660	585	16	39	50		945	400	285
500	700	670	620	20	26	28		715	650	20	33	34		775	670	20	42	52		1120	500	410

Series 1422 ... Bronze




Flanges according to DIN2501-PN16

Part Nr.	Material	Code
1 - Body	Bronze	DIN 1705
2 - Disc	Bronze	DIN 1705
3 - Stem	Brass	DIN 17672

Size	Series 1422 L	D	C	Holes	H	KG
15	75	95	65	4 x 14	90	1.5
20	82	105	75	4 x 14	115	2.0
25	90	115	85	4 x 14	130	2.5
32	100	140	100	4 x 18	145	4.0
40	110	150	110	4 x 18	160	5.5
50	125	165	125	4 x 18	190	7.2
65	145	185	145	4 x 18	230	10.0
80	160	200	160	8 x 18	260	14.0
100	175	220	180	8 x 18	335	22.0
125	-	250	210	8 x 18	395	28.0
150	-	285	240	8 x 22	415	38.0

Series 2002 ... Regular

Series 2102 ... SDNR



Face to Face according to ISO5752 Series 1


Flanges according to DIN2501-PN16

Part Nr.	Material	Code	Size DN	Nom. Pressure		Hydraulic Inspection	
				PN		Body	Seat
1 - Body	Cast Iron	GG25	15 to 250	16		25	16
2 - Stem	Stainless Steel	INOX	300	10		16	10
3 - Disc	Stainless Steel	INOX					
4 - Seat	Stainless Steel	INOX					

Size	L	D	C	No.	h	t	H	D2	Kg
15	130	95	65	4	14	14	160	100	3.8
20	150	105	75	4	14	16	165	100	5
25	160	115	85	4	14	16	190	125	5.7
32	180	140	100	4	18	16	200	125	8.2
40	200	150	110	4	18	16	225	150	10
50	230	165	125	4	18	18	260	150	13.5
65	290	185	145	4	18	18	280	200	22
80	310	200	160	8	18	20	320	200	25
100	350	220	180	8	18	20	375	225	38.5
125	400	250	210	8	18	22	415	225	55
150	480	285	240	8	22	22	460	300	78
175	550	315	270	8	22	24	550	300	110
200	600	340	295	12	22	24	570	420	125
250	730	405	355	12	25	26	750	500	250
300	850	460	410	12	25	26	900	500	340

Series 2012 ... Regular

Series 2112 ... SDNR




Face to Face according to ISO5752, Series 1
Flanges according to DIN2501-PN16

Part Nr.	Material	Code	Size DN	Nom. Pressure PN	Hydraulic Inspection	
					Body	Seat
1 - Body	Cast Steel	GSC-25N	15 to 250	16	25	16
2 - Stem	Stainless Steel	INOX				
3 - Disc	Stainless Steel	INOX	300	10	16	10
4 - Seat	Stainless Steel	INOX				

Size	L	D	C	No.	h	t	H	D2	Kg
15	130	95	65	4	14	14	160	100	3.8
20	150	105	75	4	14	16	165	100	5
25	160	115	85	4	14	16	190	125	5.7
32	180	140	100	4	18	16	200	125	8.2
40	200	150	110	4	18	16	225	150	10
50	230	165	125	4	18	18	260	150	13.5
65	290	185	145	4	18	18	280	200	22
80	310	200	160	8	18	20	320	200	25
100	350	220	180	8	18	20	375	225	38.5
125	400	250	210	8	18	22	415	225	55
150	480	285	240	8	22	22	460	300	78
175	550	315	270	8	22	24	550	300	110
200	600	340	295	12	22	24	570	420	125
250	730	405	355	12	25	26	750	500	250
300	850	460	410	12	25	26	900	500	340

Series 2015 ... Regular

Series 2115 ... SDNR




Face to Face according to ISO5752, Series 1
Flanges according to DIN2501-PN40

Part Nr.	Material	Code	Size DN	Nom. Pressure PN	Hydraulic Inspection	
					Body	Seat
1 - Body	Cast Steel	GSC-25N	15 to 175	40	60	40
2 - Stem	Stainless Steel	AISI 410	200 to 300	25	37.5	25
3 - Disc	Stainless Steel	AISI 410				
4 - Seat	Stainless Steel	AISI 410				

Size	L	D	C	No.	h	t	H	D2	Kg
15	130	95	65	4	14	16	160	100	4.4
20	150	105	75	4	14	18	165	100	5.7
25	160	115	85	4	14	18	190	125	6.8
32	180	140	100	4	18	18	200	125	8.3
40	200	150	110	4	18	18	225	150	11
50	230	165	125	4	18	20	260	150	16
65	290	185	145	8	18	22	280	200	27
80	310	200	160	8	18	24	320	200	31
100	350	235	190	8	22	24	375	250	48
125	400	270	220	8	25	26	415	250	58
150	480	300	250	8	25	28	460	300	86
175	550	350	295	12	30	32	550	420	132
200	600	375	320	12	30	34	570	420	160
250	730	450	385	12	33	38	750	500	360
300	850	515	450	16	33	42	900	575	480

Series 2017 ... Regular
Series 2117 ... SDNR




Face to Face according to ISO5752-F1
Flanges according to DIN2501-PN100

Part Nr.	Material	Code	Size DN	Nom. Pressure PN	Hydraulic Inspection	
					Body	Seat
1 - Body	Cast Steel	GSC-25N	15 to 150	100	150	100
2 - Stem	Stainless Steel	AISI 410				
3 - Disc	Stellited	HF				
4 - Seat	Stellited	HF				

Size	L	D	C	No.	h	t	H	D2	Kg
15	210	105	75	4	14	20	250	150	9
20	230	130	90	4	18	24	310	150	12.5
25	230	140	100	4	18	24	310	150	13
32	260	155	110	4	22	28	330	200	22.5
40	260	170	125	4	22	28	350	200	23
50	300	195	145	4	26	30	400	200	29
65	340	220	170	8	26	34	480	225	55
80	380	230	180	8	26	36	510	250	73
100	430	265	210	8	30	40	580	300	106
125	500	315	250	8	33	44	600	420	168
150	550	355	290	12	33	50	630	500	246

Series 2018 ... Regular

Series 2118 ... SDNR




Face to Face according to ISO5752-F1

Flanges according to DIN2501-PN160

Part Nr.	Material	Code	Size	Nom. Pressure	Hydraulic Inspection	
1 - Body	Cast Steel	GSC-25N	DN	PN	Body	Seat
2 - Stem	Stainless Steel	AISI 410				
3 - Disc	Stellited	HF				
4 - Seat	Stellited	HF	15 to 150	160	240	160

Size	L	D	C	No.	h	t	H	D2	Kg
15	210	105	75	4	14	20	250	150	9
20	230	130	90	4	18	24	310	150	12.5
25	230	140	100	4	18	24	310	150	13
32	260	155	110	4	22	28	330	200	22.5
40	260	170	125	4	22	28	350	200	23
50	300	195	145	4	26	30	400	200	29
65	340	220	170	8	26	34	480	225	55
80	380	230	180	8	26	36	510	250	73
100	430	265	210	8	30	40	580	300	106
125	500	315	250	8	33	44	600	420	168
150	550	355	290	12	33	50	630	500	246

Series 2022 ... Regular
Series 2122 ... SDNR




Face to Face according to ISO5752 Series 1
Flanges according to DIN2501-PN16

Part Nr.	Material	Code	Size DN	Nom. Pressure PN	Hydraulic Inspection	
					Body	Seat
1 - Body	Gunmetal	DIN 1705	15 to 175	16	25	16
2 - Disc	Gunmetal	DIN 1705				
3 - Stem	Brass	DIN 17672	200 to 300	10	16	10

Size	L	D	C	No.	h	t	H	D2	Kg
15	130	95	65	4	14	14	160	100	5
20	150	105	75	4	14	16	165	100	5.5
25	160	115	85	4	14	16	190	125	6
32	180	140	100	4	18	16	200	125	8
40	200	150	110	4	18	16	225	150	10
50	230	165	125	4	18	18	260	150	12
65	290	185	145	4	18	18	280	200	17
80	310	200	160	8	18	20	320	200	23
100	350	220	180	8	18	20	375	225	30
125	400	250	210	8	18	22	415	225	50
150	480	285	240	8	22	22	460	300	65
175	550	315	270	8	22	24	550	300	85
*200	600	340	295	8	22	24	570	420	110
*250	730	395	350	12	22	26	750	500	165
*300	850	445	400	12	22	28	900	500	295

*Flanges as per DIN PN10

Series 2032 ... Regular
Series 2132 ... SDNR




Face to Face according to ISO5752 Series 1
Flanges according to DIN2501-PN16

Part Nr.	Material	Code
1 - Body	Ductile Iron	GGG40
2 - Stem	Stainless Steel	INOX
3 - Disc	Stainless Steel	INOX
4 - Seat	Stainless Steel	INOX

Size DN	Nom. Pressure	Hydraulic Inspection	
	PN	Body	Seat
15 to 250	16	25	16
300	10	16	10

Size	L	D	C	No.	h	t	H	D2	Kg
15	130	95	65	4	14	14	160	100	3.8
20	150	105	75	4	14	16	165	100	5
25	160	115	85	4	14	16	190	125	5.7
32	180	140	100	4	18	16	200	125	8.2
40	200	150	110	4	18	16	225	150	10
50	230	165	125	4	18	18	260	150	13.5
65	290	185	145	4	18	18	280	200	22
80	310	200	160	8	18	20	320	200	25
100	350	220	180	8	18	20	375	225	38.5
125	400	250	210	8	18	22	415	225	55
150	480	285	240	8	22	22	460	300	78
175	550	315	270	8	22	24	550	300	110
200	600	340	295	12	22	24	570	420	125
250	730	405	355	12	25	26	750	500	250
300	850	460	410	12	25	26	900	500	340

Series 3002 ... Regular
Series 3102 ... SDNR




Face to Center according to ISO5752 Series 8
Flanges according to DIN2501-PN16

Part Nr.	Material	Code	Size DN	Nom. Pressure		Hydraulic Inspection	
				PN		Body	Seat
1 - Body	Cast Iron	GG25	15 to 250	16		25	16
2 - Stem	Stainless Steel	INOX					
3 - Disc	Stainless Steel	INOX	300	10		16	10
4 - Seat	Stainless Steel	INOX					

Size	L1	D	C	No.	h	t	H	D2	Kg
15	90	95	65	4	14	14	130	100	3.9
20	95	105	75	4	14	16	135	100	4.5
25	100	115	85	4	14	16	160	125	5.5
32	105	140	100	4	18	16	170	125	6.6
40	115	150	110	4	18	16	200	150	9.1
50	125	165	125	4	18	18	225	150	11.5
65	145	185	145	4	18	18	260	200	17.1
80	155	200	160	8	18	20	280	200	23
100	175	220	180	8	18	20	325	225	32
125	200	250	210	8	18	22	355	225	46
150	225	285	240	8	22	22	385	300	67
175	250	315	270	8	22	24	470	300	92
200	275	340	295	12	22	24	500	420	126
250	325	405	355	12	25	26	580	500	184
300	375	460	410	12	25	26	630	500	270

Series 3012 ... Regular

Series 3112 ... SDNR




Face to Center according to ISO5752 Series 8

Flanges according to DIN2501-PN16

Part Nr.	Material	Code	Size DN	Nom. Pressure PN	Hydraulic Inspection	
					Body	Seat
1 - Body	Cast Steel	GSC-25N	15 to 250	16	25	16
2 - Stem	Stainless Steel	INOX				
3 - Disc	Stainless Steel	INOX	300	10	16	10
4 - Seat	Stainless Steel	INOX				

Size	L1	D	C	No.	h	t	H	D2	Kg
15	90	95	65	4	14	14	130	100	3.9
20	95	105	75	4	14	16	135	100	4.5
25	100	115	85	4	14	16	160	125	5.5
32	105	140	100	4	18	16	170	125	6.6
40	115	150	110	4	18	16	200	150	9.1
50	125	165	125	4	18	18	225	150	11.5
65	145	185	145	4	18	18	260	200	17.1
80	155	200	160	8	18	20	280	200	23
100	175	220	180	8	18	20	325	225	32
125	200	250	210	8	18	22	355	225	46
150	225	285	240	8	22	22	385	300	67
175	250	315	270	8	22	24	470	300	92
200	275	340	295	12	22	24	500	420	126
250	325	405	355	12	25	26	580	500	184
300	375	460	410	12	25	26	630	500	270

Series 3015 ... Regular
Series 3115 ... SDNR




Face to Center according to ISO5752 Series 8
Flanges according to DIN2501-PN40

Part Nr.	Material	Code	Size DN	Nom. Pressure PN	Hydraulic Inspection	
					Body	Seat
1 - Body	Cast Steel	GSC-25N	15 to 175	40	60	40
2 - Stem	Stainless Steel	AISI 410	200 to 300	25	37.5	25
3 - Disc	Stainless Steel	AISI 410				
4 - Seat	Stainless Steel	AISI 410				

Size	L1	D	C	No.	h	t	H	D2	Kg
15	90	95	65	4	14	16	130	100	5.6
20	95	105	75	4	14	18	135	110	7.6
25	100	115	85	4	14	18	160	125	7.9
32	105	140	100	4	18	18	170	125	8.9
40	115	150	110	4	18	18	200	150	13.4
50	125	165	125	4	18	20	225	150	14.4
65	145	185	145	8	18	22	260	200	24
80	155	200	160	8	18	24	280	200	29
100	175	235	190	8	22	24	325	250	44
125	200	270	220	8	25	26	355	250	59
150	225	300	250	8	25	28	385	300	85
175	250	350	295	12	30	32	470	420	123
200	275	375	320	12	30	34	500	420	148
250	325	450	385	12	33	38	580	500	188
300	375	515	450	16	33	42	630	575	328

Series 3022 ... Regular
Series 3122 ... SDNR



Face to Center according to ISO5752 Series 8
Flanges according to DIN2501-PN16


Part Nr.	Material	Code	DN	Nom. Pressure PN	Hydraulic Inspection	
					Body	Seat
1 - Body	Gunmetal	DIN 1705	15 to 175	16	25	16
2 - Disc	Gunmetal	DIN 1705	200 to 300	10	16	10
3 - Stem	Brass	DIN 17672				

Size	L	D	C	No.	h	t	H	D2	Kg
15	90	95	65	4	14	14	160	100	3.2
20	95	105	75	4	14	16	165	100	4.2
25	100	115	85	4	14	16	190	125	4.5
32	105	140	100	4	18	16	200	125	7.6
40	115	150	110	4	18	16	225	150	8
50	125	165	125	4	18	18	260	150	12
65	145	185	145	4	18	18	280	200	17.5
80	155	200	160	8	18	20	320	200	24
100	175	220	180	8	18	20	375	225	32
125	200	250	210	8	18	22	415	225	51
150	225	285	240	8	22	22	460	300	74
175	250	315	270	8	22	24	550	300	107
*200	275	340	295	8	22	24	570	420	135
*250	325	395	350	12	22	26	750	500	175
*300	325	445	400	12	22	28	900	500	205

*Flanges as per DIN N10

Series 3032 ... Regular

Series 3132 ... SDNR



Face to Center according to ISO5752 Series 8


Flanges according to DIN2501-PN16

Part Nr.	Material	Code	Size DN	Nom. Pressure		Hydraulic Inspection	
				PN		Body	Seat
1 - Body	Ductile Iron	GGG40	15 to 250	16		25	16
2 - Stem	Stainless Steel	INOX	300	10		16	10
3 - Disc	Stainless Steel	INOX					
4 - Seat	Stainless Steel	INOX					


Size	L1	D	C	No.	h	t	H	D2	Kg
15	90	95	65	4	14	14	130	100	3.9
20	95	105	75	4	14	16	135	100	4.5
25	100	115	85	4	14	16	160	125	5.5
32	105	140	100	4	18	16	170	125	6.6
40	115	150	110	4	18	16	200	150	9.1
50	125	165	125	4	18	18	225	150	11.5
65	145	185	145	4	18	18	260	200	17.1
80	155	200	160	8	18	20	280	200	23
100	175	220	180	8	18	20	325	225	32
125	200	250	210	8	18	22	355	225	46
150	225	285	240	8	22	22	385	300	67
175	250	315	270	8	22	24	470	300	92
200	275	340	295	12	22	24	500	420	126
250	325	405	355	12	25	26	580	500	184
300	375	460	410	12	25	26	630	500	270

Series 2222 ... Globe

Series 3222 ... Angle



Series 2222




Series 3222

Manufactured as per DIN 86211
Flanges according to DIN2501-PN16

Part Nr.	Material	Code	Size	Nom. Pressure	Hydraulic Inspection	
1 - Body	Gunmetal	DIN 1705	DN	PN	Body	Seat
2 - Disc	Gunmetal	DIN 1705				
3 - Stem	Brass	DIN 17672				
4 - Coupling	Brass	DIN 17672				
			40 to 65	16	25	16

Type	Size	L	D	C	No.	h	t	H	D2	Kg
Series 2222	40	150	150	110	4	18	18	160	140	6.2
	50	165	165	125	4	18	18	155	140	6.8
	65	200	185	145	4	18	18	185	160	11.7
Series 3222	40	75	150	110	4	18	18	152	140	6.2
	50	75	165	125	4	18	18	140	140	6.5
	65	95	185	145	4	18	18	165	160	10.8

Series 2312 ... Globe
Series 3312 ... Angle



Flanges according to DIN2501-PN16


Part Nr.	Material	Code
1 - Body	Cast Steel	GSC-25N
2 - Disc	Stainless Steel	INOX
3 - Stem	Stainless Steel	INOX

Size	Nom. Pressure	Hydraulic Inspection	
DN	PN	Body	Seat
20 to 150	16	25	16
200 to 300	10	16	10

Size	L	L 1	D	H	H 1	D 2	Weight	
							Globe	Angle
20	150	95	105	300	290	100	6 Kg	7 Kg
25	160	100	115	335	325	100	7 Kg	8 Kg
32	180	105	140	355	340	100	8 Kg	11 Kg
40	200	115	150	375	355	100	10 Kg	14 Kg
50	230	125	165	400	380	100	13 Kg	15 Kg
65	290	145	185	435	400	140	19 Kg	28 Kg
80	310	155	200	475	440	140	27 Kg	35 Kg
100	350	175	220	525	485	160	36 Kg	45 Kg
125	400	200	250	585	530	160	56 Kg	70 Kg
150	480	225	285	640	575	200	78 Kg	94 Kg
200	600	275	340	770	670	200	140 Kg	141 Kg
250	730	325	405	900	820	395	215 Kg	310 Kg
300	850	375	460	1240	1180	395	360 Kg	360 Kg

Series 2415 ... Globe

Series 3415 ... Angle




Flanges according to DIN2501-PN40

Part Nr.	Material	Code
1 - Body	Cast Steel	GSC-25N
2 - Disc	Stainless Steel	INOX
3 - Seat	Stainless Steel	INOX
4 - Stem	Stainless Steel	INOX


Size DN	Spring loaded Shut-off Pressure	Working Pressure
15 to 80	2.0 Bar	40 Bar
100 to 150	1.2 Bar	40 Bar

Size DN	L	L 1	D	H	H 1	D 2	Weight	
							Globe	Angle
15	130	90	95	230	200	100	6 Kg	6 Kg
20	150	95	105	300	290	100	7 Kg	7 Kg
25	160	100	115	335	325	100	8 Kg	8 Kg
32	180	105	140	355	340	100	11 Kg	11 Kg
40	200	115	150	375	355	100	14 Kg	14 Kg
50	230	125	165	400	380	100	19 Kg	18 Kg
65	290	145	185	435	400	140	31 Kg	30 Kg
80	310	155	200	475	440	140	34 Kg	36 Kg
100	350	175	220	525	485	160	49 Kg	50 Kg
125	400	200	250	585	530	160	71 Kg	71 Kg
150	480	225	285	640	575	200	99 Kg	101 Kg

Series 2522 ... Globe
Series 3522 ... Angle



Series 2522




Series 3522

Flanges according to DIN2501-PN16


Part Nr.	Material	Code	Size DN	Nom. Pressure PN	Hydraulic Inspection	
					Body	Seat
1 - Body 2 - Disc 3 - Stem	Gunmetal Gunmetal Brass	DIN 1705 DIN 1705 DIN 17672	15 to 100	16	25	16

Size	L	L1	D	C	No.	h	t	H	D2	2522 Kg	3522 Kg
15	70	62	95	65	4	14	14	115	60	1.5	1.9
20	90	65	105	75	4	14	16	125	70	2.3	3
25	98	72	115	85	4	14	16	140	90	2.7	3.8
32	110	85	140	100	4	18	18	155	90	4.5	5.7
40	130	90	150	110	4	18	19	175	110	6.3	6.2
50	150	103	165	125	4	18	20	195	120	8	9.7
65	190	116	185	145	4	18	20	225	160	11.6	12.2
80	210	122	200	160	8	18	22	225	160	16	16
100	220	140	220	180	8	18	24	280	160	21	-

Series 2722 ... Globe
Series 3722 ... Angle



Series 2722




Series 3722

Flanges according to DIN2501-PN16

Part Nr.	Material	Code	Size		Nom. Pressure		Hydraulic Inspection	
			DN		PN		Body	Seat
1 - Body	Gunmetal	DIN 1705	15 to 175		16		25	16
2 - Stem	Brass	DIN 17672						
3 - Disc	Gunmetal	DIN 1705	200 to 300		10		16	10

Size	L	L1	D	C	No.	h	t	H	D2	2722 Kg	3722 Kg
15	120	65	95	65	4	14	14	160	100	4	4
20	120	65	105	75	4	14	16	160	100	5	5
25	140	70	115	85	4	14	16	175	125	6	6
32	150	90	140	100	4	18	18	175	125	8	8
40	155	90	150	110	4	18	19	210	150	10	10
50	180	105	165	125	4	18	20	215	150	13	12
65	200	115	185	145	4	18	20	235	200	23	23
80	240	125	200	160	8	18	22	275	200	32	31
100	270	145	220	180	8	18	24	325	225	42	41
125	320	170	250	210	8	18	26	360	225	62	65
150	370	200	285	240	8	22	26	405	300	88	89
175	450	225	315	270	8	22	28	520	300	106	96
200	500	250	340	295	8	22	30	600	420	136	127

Series 4012 ... Carbon Steel




For mounting between flanges according to Din2501-PN16

Material		
Part Nr.	Material	Code
1 - Body	Carbon Steel	GSC - 25N
2 - Disc	Stainless Steel	AISI 316L
3 - Arm	Stainless Steel	AISI 316L
4 - Seat	Viton	FKM
5 - Spring	Stainless Steel	AISI 316L

Size DN	Nom. Pressure	Hydraulic Inspection	
	PN	Body	Seat
40 to 200	16	25	16
250 to 500	10	16	10

Size	L	D	D2	Kg
50	45	109	33	1.8
65	48	129	43	2.4
80	51	144	52	3.2
100	57	164	76	5.4
125	64	194	95	7.3
150	70	220	121	9.2
200	73	275	164	14.6
250	79	331	194	23.6
300	86	386	241	34.4
350	108	446	267	75.0
400	108	498	318	91.0
450	108	558	356	100.0
500	140	620	387	154.0

Series 4022 ... Bronze
Series 4052 ... Stainless Steel




For mounting between flanges according to DIN2501-PN16

Size DN	Nom. Pressure PN	Hydraulic Inspection	
		Body	Seat
40 to 200	16	25	16
250 to 500	10	16	10

Available Material Combinations		
Part Nr.	Material	Code
1 - Body	Gunmetal	DIN 1705
	Stainless Steel	AISI 316L
2 - Disc	Gunmetal	DIN 1705
	Stainless Steel	AISI 316L
3 - Seat	NBR	NBR
	EPDM	EPDM
	Viton	FKM
	Teflon	PTFE

Size	L	D	D2	Kg
40	14	94	26	.9
50	14	109	26	.9
65	14	129	38	1.3
80	14	144	47	1.5
100	18	164	70	2
125	18	195	92	3
150	20	221	114	4.8
200	22	276	143	11
250	26	330	190	15
300	32	386	214	25
350	38	446	263	37
400	44	498	305	55
450	50	558	342	65
500	56	620	400	105

Series 4101 ... Cast Iron
Series 4111 ... Cast Steel




Part Nr.	Series 4101		Series 4111	
	Material	Code	Material	Code
1 - Body	Cast Iron	GG25	Cast Steel	GSC-25N
2 - Disc	Bronze	RG5	Stainless Steel	316
3 - Spring	Stainless Steel	316	Stainless Steel	316
4 - Seat Ring	NBR	NBR	NBR	NBR
	Viton	Viton		


Size	Series 4101 Series 4111 L	A	E	Kg
50	43	98	66	2.7
65	46	110	80	4.5
80	64	128	100	5.9
100	64	156	112	7.7
125	70	187	135	12
150	76	213	160	16
200	89	267	210	32
250	114	328	260	48
300	114	375	310	78
350	127	415	360	91
400	140	82	410	125
450	203	549	460	143
500	212	606	511	197

Series 4211 ... Vertical

Series 4311 ... Angle



Series 4211



Series 4311


Flanges according to DIN2501-PN10

Part Nr.		Material		Code	
1 - Body		Cast Steel		GSC-25N	
2 - Disc		Bronze		DIN 1705	
3 - Disc Gasket		NBR		NBR	
4 - Stem		Brass		DIN 17672	

Size	DN	Nom. Pressure		Hydraulic Inspection	
		PN		Body	Seat
50 to 200		10		5.1	2.0

Type	Size	L	D	C	No.	h	t	d1	D1	C1	No1	h1	t1	H	D2	Kg.
4211 Vertical	50	200	165	125	4	18	18	-	-	-	-	-	-	356	100	19.9
	65	240	185	145	4	18	18	-	-	-	-	-	-	396	100	28.7
	80	260	200	160	8	18	20	-	-	-	-	-	-	450	100	32.4
	100	300	220	180	8	18	20	-	-	-	-	-	-	490	100	48.7
	125	350	250	210	8	18	22	-	-	-	-	-	-	572	125	73.1
	150	400	285	240	8	22	22	-	-	-	-	-	-	622	125	104
	200	500	340	295	8	22	24	-	-	-	-	-	-	720	125	189
4311 Angle	50	180	165	125	4	18	18	68	200	160	8	18	20	210	100	11.5
	65	200	185	145	4	18	18	85	220	180	8	18	20	220	100	13.5
	80	215	200	160	8	18	20	100	250	210	8	18	22	233	100	18
	100	250	220	180	8	18	20	130	285	240	8	22	22	255	100	27
	125	290	250	210	8	18	22	158	315	270	8	22	22	292	125	36.5
	150	330	285	240	8	22	22	190	340	295	8	22	24	316	125	480

Series 4402 ... Regular



Face to Face according to DIN 3202-F6
Flanges according to DIN2501-PN16


Part Nr.	Material	Code
1 - Body	Cast Iron	GG25
2 - Hinge	Cast Iron	GG25
3 - Disc	Brass	UNI 5035
4 - Seat	Brass	UNI 5035

Size DN	Nom. Pressure	Hydraulic Inspection	
	PN	Body	Seat
40 to 300	16	24	16
350 to 400	10	16	10

Size	L	D	C	No.	h	t	H	Kg
40	180	150	110	4	18	16	115	19
50	200	165	125	4	18	18	125	22
65	240	185	145	4	18	18	130	29
80	260	200	160	8	18	20	140	30
100	300	220	180	8	18	20	160	33
125	350	250	210	8	18	22	180	45
150	400	285	240	8	22	22	200	57
200	500	340	295	12	22	24	220	155
250	600	405	355	12	26	26	290	185
300	700	460	410	12	26	28	330	307
350*	800	505	460	16	22	26	435	413
400*	900	565	515	16	26	26	475	520

*PN10 Drilling for sizes DN 350 and DN 400

Series 4412 ... Regular




Face to Face according to DIN 3202-F6

Flanges according to DIN2501-PN16


Part Nr.	Material	Code	Size	Nom. Pressure	Hydraulic Inspection	
					Body	Seat
1 - Body	Cast Steel	GSC-25N	DN	PN	24	16
2 - Hinge	Stainless Steel	AISI 410				
3 - Disc	Stainless Steel	AISI 410	40 to 250	16	24	16
4 - Seat	Stainless Steel	AISI 410				

Size	L	D	C	No.	h	t	H	Kg
40	180	150	110	4	18	16	105	12
50	200	165	125	4	18	18	110	14
65	240	185	145	4	18	18	140	19
80	260	200	160	8	18	20	145	23
100	300	220	180	8	18	20	160	35
125	350	250	210	8	18	22	180	43
150	400	285	240	8	22	22	195	67
200	500	340	295	12	22	24	245	99
250	600	405	355	12	26	26	285	149

Series 4602 ... Globe
Series 4702 ... Angle



Series 4602



Series 4702

Face to Face according to DIN 3202-F1
Face to Center according to DIN 3202 - F8
Flanges according to DIN2501-PN16


Part Nr.	Material	Code
1 - Body	Cast Iron	GG25
2 - Disc	Stainless Steel	AISI 410
3 - Seat	Stainless Steel	AISI 410

Size	Nom. Pressure	Hydraulic Inspection	
DN	PN	Body	Seat
15 to 200	16	24	16


Size	L	L1	D	C	No.	h	t	H	Kg
15	130	90	95	65	4	14	14	75	2.2
20	150	95	105	75	4	14	16	75	3
25	160	100	115	85	4	14	16	75	3.6
32	180	105	140	100	4	18	16	80	5
40	200	115	150	110	4	18	16	85	7.5
50	230	125	165	125	4	18	18	95	9.5
65	290	145	185	145	4	18	18	120	16
80	310	155	200	160	8	18	20	130	20
100	350	175	220	180	8	18	20	155	31
125	400	200	250	210	8	18	22	180	48
150	480	225	285	240	8	22	22	200	67
200	600	275	340	295	12	22	24	260	152

Series 4615 ... Globe

Series 4715 ... Angle



Series 4615



Series 4715



Face to Face according to DIN 3202-F1
Face to Center according to DIN 3202-F8
Flanges according to DIN2501-PN40

Part Nr.	Material	Code
1 - Body	Cast Steel	GSC-25N
2 - Disc	Stainless Steel	AISI 410
3 - Seat	Stainless Steel	AISI 410

Size	Nom. Pressure	Hydraulic Inspection	
DN	PN	Body	Seat
15 to 200	40	60	40

Size	L	L1	D	C	No.	h	t	H	Kg
15	130	90	95	65	4	14	16	75	3
20	150	95	105	75	4	14	18	75	4
25	160	100	115	85	4	14	18	75	5
32	180	105	140	100	4	18	18	80	7
40	200	115	150	110	4	18	18	85	9.7
50	230	125	165	125	4	18	20	95	13
65	290	145	185	145	8	18	22	120	21
80	310	155	200	160	8	18	24	130	29
100	350	175	235	190	8	22	24	155	43
125	400	200	270	220	8	25	26	180	70
150	480	225	300	250	8	25	28	200	98
200	600	275	375	320	12	30	34	260	188

Series 4822 ... Bronze ... PN 6 - PN 16
Series 4865 ... Stainless Steel ... PN 6 - PN 40



Face to face according to DIN3202 K4


Part Nr.	Material	Code
1 - Body	Bronze	B-584
2 - Disc	Stainless Steel	AISI 316 L
3 - Spring	Stainless Steel	AISI 316 L
4 - Spring stop ring	Stainless Steel	AISI 316 L

DN 4822						
Size	d	d - 1	D	A	L	Weight
15	32	15	53	37	16	0.11
20	39	20	63	45	19	0.14
25	46	24	73	55	22	0.26
32	57	31	84	65	28	0.36
40	65	38	94	74	32	0.46
50	80	47	107	89	40	0.90
65	97	62	126	107	46	1.60
80	113	77	144	126	50	2.10
100	127	95	162	147	60	2.80

Part Nr.	Material	Code
1 - Body	Stainless Steel	AISI 316 L
2 - Disc	Stainless Steel	AISI 316 L
3 - Spring	Stainless Steel	AISI 316 L
4 - Seat	Stainless Steel	AISI 316 L

DN 4865					
Size	d	D	A	L	Weight
15	15	53	45	16	0.11
20	20	63	55	19	0.14
25	24	73	65	22	0.26
32	31	84	74	28	0.40
40	38	94	84	32	0.60
50	47	107	98	40	1.00
65	62	126	118	46	1.30
80	77	144	130	50	1.90
100	95	162	156	60	3.40

Series 4901 ... Cast Iron



Flanges according to DIN2501-PN10

Part Nr.	Material	Code
1 - Body	Cast Iron	FC
2 - Disc	Stainless Steel	SUS 304
3 - Screen Cover	Stainless Steel	SS 41
4 - Wire Net	Stainless Steel	SUS 304
5 - Guide Bar	Stainless Steel	SUS 304

Size	d	D	C	Holes	H	KG
100	100	220	180	8 x 18	231	18
125	125	250	210	8 x 18	266	28
150	150	285	240	8 x 22	311	39
200	200	340	295	8 x 22	367	74
250	250	395	350	12 x 22	453	105
300	300	445	400	12 x 22	524	146
350	350	505	460	16 x 22	595	199

Cast Iron

Series 6202 ... PN 16

Cast Steel


Series 6212 ... PN 16

Series 6215 ... PN 40

Stainless Steel

Series 6252 ... PN 16

Series 6255 ... PN 40




Face to Face according to DIN 3202-F4/5

Flanges according to DIN2501-PN16 & 40

Part Nr.	Cast Iron		Cast Steel		Stainless Steel		Size DN	Nominal Pressure PN	Hydraulic Inspection	
	Material	Code	Material	Code	Material	Code			Body	Seat
1 - Body	Cast Iron	GG25	Steel	WCB	SS316	CF8M	15 -150	16	25	16
2 - Ball	Brass	Ms58	SS316	CF8M	SS316	CF8M				
3 - Seat	Teflon	PTFE	Teflon	PTFE	Teflon	PTFE	15 -150	40	64	40

Size				DIN PN16 (Iron - Steel - Stainless Steel)					DIN PN40 (Steel - Stainless Steel)					Iron Kg	Steel &SS Kg
	L	H	D2	D	C	No.	h	t	D	C	No.	h	t		
15	200	60	130	Same as DIN PN40				14	95	65	4	14	16	2.0	2.5
20	120	70	130	Same as DIN PN40				16	105	75	4	14	18	2.5	3.5
25	125	84	225	Same as DIN PN40				16	115	85	4	14	18	3.2	4.5
32	130	89	225	Same as DIN PN40				16	140	100	4	18	18	4.4	7
40	140	95	225	Same as DIN PN40				16	150	110	4	18	18	5.5	8
50	150	130	333	Same as DIN PN40				18	165	125	4	18	20	8.5	12
65	170	140	333	Same as DIN PN40				18	185	145	8	18	22	11.5	16
80	180	175	395	Same as DIN PN40				20	200	160	8	18	24	15.5	21
100	190	190	395	220	180	8	18	20	235	190	8	22	24	20	40
125	200	320	600	250	210	8	18	22	270	220	8	25	26	30	60
150	210	350	800	285	240	8	22	22	300	250	8	25	28	36	100

Series 80 ... Flanged




Flanges according to DIN2501

Part Nr.	Material	Code	Size	Max. Inlet Pressure	Reducer Pressure
1 - Body	Bronze	DIN 1705	DN15 - DN40	30 / 25 Bar	1.5 - 12 Bar
2 - Disc & Seat	Synthetic Material	Synthetic	DN50 - DN150	16 Bar	1.5 - 6 Bar
3 - Stem	Brass	DIN 17672			
4 - Cap	Bronze	DIN 1705			

Size	L	D	C	Holes	H	Weight
15	130	95	65	4 x 14	103	6.4
20	150	105	75	4 x 14	103	7.9
25	160	115	85	4 x 14	141	12.3
32	180	140	100	4 x 18	141	16.5
40	200	150	110	4 x 18	172	20.8
50	230	165	125	4 x 18	330	35.6
65	290	185	145	4 x 18	370	62.0
80	310	200	160	8 x 18	400	91.5
100	350	220	180	8 x 18	470	147.5
125	400	250	210	8 x 18	580	226.5
150	480	285	240	8 x 22	660	330


Series 8202 ... Cast Iron
Series 8215 ... Cast Steel



Face to Face according to DIN 3202-F1
Flanges according to DIN2501-PN16

Part Nr.	Material	Code	Size DN	Nom. Pressure PN	Hydraulic Inspection	
					Body	Seat
1 - Body 2 - Strainer	Cast Iron Stainless Steel	GG25 AISI 304	15 to 150	16	25	16
1 - Body 2 - Strainer	Cast Steel Stainless Steel	GSC-25N AISI 304	15 to 150	40	64	40

Size	L	H	DIN PN16					DIN PN40					Steel	Iron
			D	C	No.	h	t	D	C	No.	h	t	Kg	Kg
015	130	75	Same as DIN PN40				14	95	65	4	14	16	4	3.5
020	150	75	Same as DIN PN40				16	105	75	4	14	18	5	4.5
025	160	90	Same as DIN PN40				16	115	85	4	14	18	6	5
032	180	90	Same as DIN PN40				16	140	100	4	18	18	8	7.2
040	200	110	Same as DIN PN40				16	150	110	4	18	18	10	9
050	230	120	Same as DIN PN40				18	165	125	4	18	20	13	11.5
065	290	140	Same as DIN PN40				18	185	145	8	18	22	19	17
080	310	170	Same as DIN PN40				20	200	160	8	18	24	24	22
100	350	220	220	180	8	18	20	235	190	8	22	24	35	32
125	400	260	250	210	8	18	22	270	220	8	25	26	51	48
150	480	300	285	240	8	22	22	300	250	8	25	28	71	67




Part Nr.	Material	Code
1 - Body	Stainless Steel	1.4305
2 - Disc	Stainless Steel	1.4305
3 - Stem	Stainless Steel	1.4305

Working Pressure	
350 Bar	20° Celsuis
200 Bar	100° Celsuis

Size	L	d	H	M	Kg
1/8"	50	3	88	50	0.3
1/4"	50	3	88	50	0.3
3/8"	57	4	88	50	0.3
1/2"	60	6	90	50	0.4
3/4"	80	9	105	63	0.7
1"	80	9	108	63	0.8

Series XRD10 ... Rubber



Flanges according to DIN2501-PN10

Part Nr.	Material
1 - Body	NBR Rubber
2 - Flanges	Galvanized Mild Steel

Size	L	D	C	Holes	KG
32	95	140	100	4 x 18	3.3
40	95	150	110	4 x 18	3.3
50	105	165	125	4 x 18	4.1
65	115	185	145	4 x 18	4.5
80	130	200	160	8 x 18	6.8
100	135	220	180	8 x 18	7.3
125	170	250	210	8 x 18	8.2
150	180	285	240	8 x 22	12.0
200	205	340	295	8 x 22	17
250	240	395	350	12 x 22	24
300	260	445	400	12 x 22	26

**Available Materials for Butterfly Valve Series:
50, 52, 53, 54, 55, 56 and 58**

<u>Part</u>	<u>Material</u>	<u>DIN Code</u>	<u>ASTM Code</u>
Body:	Cast Iron	GG 25	ASTM A126 Cl. B
	Ductile Iron	GGG 40	ASTM A536 Gr 65-45-12
	Carbon Steel	GS-C 25	ASTM A216 WCB
	Stainless Steel	G-X6 CrNiMo 18.10	ASTM A351 Gr CF8-CF8M
	Bronze	RG5	ASTM B62
Disc:	Ductile Iron	GGG 40	ASTM A536 Gr 65-45-12
	Stainless Steel	G-X6 CrNiMo 18.10	ASTM A351 Gr CF8-CF8M
	Aluminum Bronze	G-CuAl10Ni	ASTM B 148 Cl. C 95500
Stem:	Stainless Steel	X2 CrNiMo 18.10	ASTM A276 316
Seat:	NBR	Nitrile Rubber	Temp Range -25° C / + 100° C
	EPDM	Copolymer EPDM	Temp Range -35° C / + 130° C
	Viton	Fluoeastomer	Temp Range -20° C / + 200° C
	Teflon	PTFE	Temp Range -80° C / + 232° C
Packing:	NBR	Nitrile Rubber	Temp Range -25° C / + 100° C
	EPDM	Copolymer EPDM	Temp Range -35° C / + 130° C
	Viton	Fluoeastomer	Temp Range -20° C / + 200° C

Chemical Agent	Bronze	Cast Iron	Cast Steel	SS316	Monel	EPDM	NBR	VITON	Natural Rubber
Acetone	E	G	G	E	E	G	U	U	E
Acetylene	E	G	G	E	-	U	F	U	-
Alcohol methyl	E	U	-	E	E	E	G	U	G
Alumina	G	G	-	G	G	E	E	G	G
Amonia solutions	U	F	-	E	G	E	G	U	G
Benzene	E	F	G	E	G	U	U	G	U
Bunker oil	F	U	U	E	E	U	F	F	U
Carbon dioxide	E	F	G	E	-	G	G	E	G
Chlorobenzene	E	F	F	E	E	U	U	G	U
Crude oil	U	U	G	E	E	U	F	E	U
Diesel fuel	F	U	E	E	E	U	E	E	U
Ethyl glycol	E	G	G	E	E	E	E	E	G
Fruit juices	U	U	-	E	-	G	G	-	-
Fuel oil	E	F	E	E	G	U	F	E	U
Gasoline	G	F	G	E	G	U	E	E	U
Glycerine glycerol	G	F	E	E	G	-	E	E	-
Hydraulic oil (petroleum based)	U	U	E	F	F	U	F	F	F
Hydraulic oil (water based)	E	U	E	E	U	E	F	U	F
Kerosene	E	E	E	E	E	U	E	E	U
Lubricating oil	E	E	E	E	E	U	E	E	U
Milk	-	U	E	E	-	E	E	E	E
Mineral oil	-	F	E	F	-	U	E	E	U
Napthalene	E	F	E	E	-	U	U	G	U

Chemical Agent	Bronze	Cast Iron	Cast Steel	SS316	Monel	EPDM	NBR	VITON	Natural Rubber
Natural gas	E	G	E	E	-	U	E	E	U
Olive oil	-	-	E	E	-	G	E	E	U
Oxygen 200 F	E	E	E	E	E	E	G	E	F
Oxygen 300 F	E	E	E	E	E	U	U	G	U
Petroleum	F	U	E	G	G	U	E	E	U
Phenol	-	U	E	E	E	U	U	E	U
Potassium nitrate	F	F	E	E	G	E	E	E	E
Potassium phosphate	-	U	-	G	-	-	E	E	-
Propane	E	F	E	E	-	U	E	E	-
Resins	E	U	-	E	-	-	-	G	F
Sea Water	G	F	F	G	E	E	G	E	-
Sodium chloride	E	U	G	E	E	E	E	E	E
Sodium nitrate	G	U	G	E	G	E	G	-	G
Steam 300 F	G	U	E	E	E	E	U	U	U
Sulphur molten	U	U	F	G	U	E	-	E	-
Sulphur dioxide	F	U	E	E	E	G	U	E	U
Sulphur trioxide	-	U	G	E	-	-	U	E	U
Tar	E	F	E	E	E	U	U	G	U
Turpentine	G	U	G	E		U	U	E	U
Varnish	E	E	E	E	E	U	F	E	U
Water distilled	U	U	G	E	-	E	G	-	-
Water fresh	E	F	G	E	E	E	G	-	E
Water sewage	E	U	G	E	E	E	G	-	-

(E) - Excellent


(G) - Good

(F) - Fair

(U) - Unsatisfactory

(-) - Insufficient Data Available

The information stated above is intended as a recommendation and suggestion based on current available data. World Wide Metric, Inc. assumes no liability or responsibility for results or damages incurred through the application of the data presented.



PN1.0/PN1.6MPa


Size		H1	H2	H3	L	ø1	ø2	ø3					ø4	n-M	n-d
								ANSI B16.1	GB9119-88	ISO2084	BS4504	DIN			
50	2"	76	162	32	45	12.7	57.15	120.65	125	125	125	125	88	—	4-ø18/ø19
65	2 1/2"	89	175	32	48	12.7	57.15	139.7	145	145	145	145	108	—	4-ø18/ø19
80	3"	95	181	32	49	12.7	57.15	152.4	160	160	160	160	118	—	4-ø18/ø19
100	4"	114	200	32	55	15.9	69.85	190.5	180	180	180	180	156	—	4-ø18/ø19
125	5"	127	213	32	58	19	69.85	215.9	210	210	210	210	181	—	4-ø18/ø22.4
150	6"	140	225	32	59	19	69.85	241.3	240	240	240	240	210	—	4-ø22/ø22.4
200	8"	177	260	45	64	22.2	88.9	298.45	295	295	295	295	260	—	4-ø22/ø22.4
250	10"	203	292	45	70	28.6	88.9	361.95	350/355	350/355	350/355	350/355	321	—	4-ø22/ø25.4
300	12"	242	337	45	80	31.7	107.95	431.8	400/410	400/410	400/410	400/410	384	—	4-ø22/ø25.4
350	14"	267	368	45	80	31.7	107.95	476.25	460/470	460/470	460/470	460/470	400	—	4-ø22/ø28.4
400	16"	298	400	51	90	33.34	158.75	539.75	515/525	515/525	515/525	515/525	465	—	4-ø22/ø28.4
450	18"	318	422	51	109	38	158.75	577.85	565/585	565/585	565/585	565/585	514	—	4-ø26/ø31.8
500	20"	349	479	64	135	41.15	158.75	635	620/650	620/650	620/650	620/650	559	—	4-ø26/ø31.8
600	24"	410	562	71	156	50.65	215.9	749.3	725/770	725/770	725/770	725/770	686	—	4-ø30/ø35.1
700	28"	520	624	72	169	55	254	—	840	840	840	840	795	—	4-ø30
800	32"	591	672	83	195	55	254	977.9	950	950	950	950	900	—	4-ø30/ø41.1
900	36"	611	768	77	211	75	254/215.9	1086	1050	1050	1050	1050	1002	—	4-ø33/ø28-41 4-1/4-7
1000	40"	665	823	85	229	85	254	—	1160	1160	1160	1160	1111	—	4-ø36
1200	48"	955	880	206	249	92	298	—	1380	—	—	—	—	4-M36	28-ø39
1400	56"	991	1015	226	390	105	298	—	1590	—	—	—	—	—	36-ø42
1600	64"	1116	1145	199	457	120	365	—	1820	—	—	—	—	4-M45	36-ø48

Note: 1. The numerator of ø3 item is 1.0Mpa, The denominator is 1.6Mpa.

2. The denominator n-d item is GB9119-88, ISO2084, BS4504. 1.0Mpa, It suitable DIN standard system. The denominator is the dimension of ANSI B16.1.

3. The H₂ dimensions may be changed into lengthened butterfly valve according to request of the users.

Overall & Connection Dimensions of Type "LT" Butterfly Valve




PN1.0/PN1.6MPa

Size		H1	H2	H3	L	Ø1	Ø2	Ø3					Ø4	n-M
								ANSI B16.1	GB 9119-88	ISO2084	BS4504	DIN		
50	2"	76	162	32	45	12.7	57.15	120.65	125	125	125	125	95	4-5/8"-11
65	2 1/2"	80	175	32	48	12.7	57.15	139.7	145	145	145	145	121	4-5/8"-11
80	3"	95	181	32	49	12.7	57.15	152.4	160	160	160	160	133	4-5/8"-11
100	4"	114	200	32	55	15.9	69.85	190.5	180	180	180	180	159	8-5/8"-11
125	5"	127	213	32	58	19	69.85	215.9	210	210	210	210	191	8-3/4"-10
150	6"	140	225	32	59	19	69.85	241.3	240	240	240	240	206	8-3/4"-10
200	8"	173	260	45	64	22.2	88.9	298.45	295	295	295	295	262	8-3/4"-10
250	10"	203	292	45	70	28.6	88.9	361.95	350/355	350/355	350/355	350/355	321	12-7/8"-9
300	12"	237	337	45	80	31.7	107.95	431.8	400/410	400/410	400/410	400/410	384	12-7/8"-9
350	14"	279	368	45	80	31.7	107.95	476.25	460/470	460/470	460/470	460/470	400	12-1"-8
400	16"	304	400	51	90	33.34	158.75	539.75	515/525	515/525	515/525	515/525	465	16-1"-8
450	18"	362	422	51	109	38	158.75	577.85	565/585	565/585	565/585	565/585	514	16-11/8"-7
500	20"	368	479	64	135	41.15	158.75	635	620/650	620/650	620/650	620/650	577	20-11/8"-7
600	24"	444	562	71	156	50.65	215.9	749.3	725/770	725/770	725/770	725/770	686	20-11/4"-7
750	30"	621	648	72	175	55	254	914.5	—	—	—	—	851	28-11/4"-7
900	36"	623	683	77	211	75	215.9	1086	—	—	—	—	977	32-11/2"-6

Note: 1. The numerator is 1.0Mpa, The denominator is 1.6Mpa.


2. The H2 dimensions may be changed into lengthened bar butterfly valve according to request of the users.

Mono Flanged type.....Series 56



Flanged type short.....Series 53


Flanged type long.....Series 54






Size						Series 56	Series 53	Series 54	Stem		Top flange to ISO 5211			
	D-1	d	H	h1	h2	L	L	L	S	T	U	V	N	M
50	165	50	215	63	118	43	108	150	10	34	90	70	4	9
65	185	65	231	71	126	46	112	170	10	34	90	70	4	9
80	200	80	245	78	133	64	114	180	10	34	90	70	4	9
100	220	100	277	98	147	64	127	190	12	34	90	70	4	9
125	250	125	303	109	160	70	140	200	12	34	90	70	4	9
150	285	150	347	133	180	76	140	210	16	34	90	70	4	9
200	340	200	396	158	204	89	152	230	16	34	90	70	4	9
250	405	250	484	194	245	114	165	250	24	45	125	102	4	11
300	460	300	534	219	270	114	178	270	24	45	125	102	4	11
350	520	336	616	256	315	127	190	290	24	45	125	102	4	11
400	580	386	721	308	363	140	216	310	30	50	175	140	4	17
450	615	436	772	334	388	152	222	330	30	50	175	140	4	17
500	670	486	823	360	413	152	229	350	30	50	175	140	4	17
600	780	586	986	426	510	178	267	390	40	50	175	140	4	17
700	906	686	1100	480	560	229	292	430	46	60	210	165	4	21
800	1021	786	1195	525	610	241	318	470	46	60	210	165	4	21

Size	Weight (KG)			PN 6			PN 10			PN 16		
	Series 56	Series 53	Series 54	D	C	bolt	D	C	bolt	D	C	bolt
50	2.8	8	10.6	140	110	4x14	165	125	4x18	165	125	4x18
65	3.6	8.5	12.5	160	130	4x14	185	145	4x18	185	145	4x18
80	6.5	9	17	190	150	4x18	200	160	8x18	200	160	8x18
100	7.5	11	20	210	170	4x18	220	180	8x18	220	180	8x18
125	11	13	26	240	200	8x18	250	210	8x18	250	210	8x18
150	14	17	31	265	225	8x18	285	240	8x22	285	240	8x22
200	18	23	45	320	280	8x18	340	295	8x22	340	295	12x22
250	28	32	70	375	335	12x18	395	350	12x22	405	355	12x26
300	38	50	90	440	395	12x22	445	400	12x22	460	410	12x26
350	50	65	120	490	445	12x22	505	460	16x22	520	470	16x26
400	95	95	165	540	495	16x22	565	515	16x26	580	525	16x30
450	115	130	200	595	550	16x22	615	565	20x26	640	585	20x30
500	155	150	230	645	600	20x22	670	620	20x26	715	650	20x33
600	230	200	320	755	705	20x26	780	725	20x30	840	770	20x36
700	330	300	420	860	810	24x26	895	840	24x30	910	840	24x36
800	430	380	610	975	920	24x30	1015	950	24x33	1025	950	24x39

Series 58



Size							Stem		Top flange ISO 5211				kg
	D	d	L	H	h1	h2	S	T	U	V	N	M	
50	102	52	43	227	67	130	10	38	90	70	4	9	4.3
65	115	65	46	241	71	140	10	38	90	70	4	9	4.5
80	128	80	46	263	83	150	10	38	90	70	4	9	4.9
100	153	100	52	290	95	163	10	38	90	70	4	9	6.3
125	183	125	56	319	110	178	12	38	90	70	4	9	8.9
150	210	150	56	347	124	191	15	38	90	70	4	9	9.4
200	259	198	60	433	163	238	18	38	90	70	4	9	11.5
250	328	248	68	546	227	285	20	45	125	102	4	12	21
300	374	298	78	601	252	315	20	45	125	102	4	12	32
350	416	327	78	675	271	324	20	45	125	102	4	12	44
400	475	387	102	817	343	369	-	60	175	140	4	18	64
450	535	438	114	877	366	406	-	60	175	140	4	18	100
500	586	477	127	1008	421	485	-	60	210	165	4	22	115
550	643	543	154	1085	440	528	-	60	210	165	4	22	164
600	695	560	154	1180	493	570	-	60	210	165	4	22	215




Technological

VALVE SIZE	BORE	A	B	WT(kg)
2" THRU 3"	12.7	266.7	31.75	0.908
4"	15.9			
5" THRU 6"	19.05			
8"	22.2	355.6	38.1	1.818
10"	28.6			
12"	31.75			


Type	A	B	C	D	E	Ø
DF24	206	154	127	105	45	152
DF30	312	238	177	153	63	300
DF50	301	222	198	162	78	300
DF80	430	300	290	260	120	300

Type	Size mm (inch)	d	t	2-b	Ø1	Ø2	4-d1
DF24	50-80 (2"-3")	12.7	14.1	3	77	57	4-M6
	100 (4")	15.87	18.1	5	92	70	4-M8
	120-150 (5"-6")	19.05	21.4	5	92	70	4-M8
DF30	200 (8")	22.2	24.8	5	115	89	4-M12
	250 (10")	28.6	31.9	8	115	89	4-M12
DF50	300-350 (12"-14")	31.8	35.1	8	140	108	4-M12
DF80	400 (16")	33.34	36.8	10	197	158.75	4-M18
	450 (18")	38.1	41.5	10	197	158.75	4-M18

Type	A	B	C	D	E	Ø
DF300	488	350	313	276	120	300
DF700	544	390	432	300	154	500



Type	Size mm (inch)	d	t	2-b	Ø	z-d
DF300	500 (20")	41.27	44.6	10	158.75	4-M18
	600 (24")	50.8	54.95	16	215.9	4-M20
DF700	700-800 (28"-32")	55.15	63.6	16	254	8-M16




Slip-On


Series DIN 2573 PN6
Series DIN 2576 PN10

Blind

Series DIN 2527 PN6 & PN10



Slip-On Type



Blind Type

DIN PN6									DIN PN10							
Size	d	D	C	No.	h	t	Weight (kg)		d	D	C	No.	h	t	Weight (kg)	
							SO	BL							SO	BL
010	17.7	75	50	4	14	12	0.27	0.30	17.7	90	60	4	14	14	0.52	0.54
015	22.2	80	55	4	14	12	0.30	0.40	22.2	95	65	4	14	14	0.57	0.61
020	27.6	90	65	4	14	14	0.37	0.50	27.6	105	75	4	14	16	0.73	0.79
025	34.4	100	75	4	14	14	0.45	0.60	34.4	115	85	4	14	16	1.13	1.24
032	43.1	120	90	4	14	16	0.78	0.90	43.1	140	100	4	18	16	1.48	1.66
040	49	130	100	4	14	16	0.83	1.00	49	150	110	4	18	16	1.56	1.81
050	61.1	140	110	4	14	16	1.07	1.40	61.1	165	125	4	18	18	1.88	2.23
065	77.1	160	130	4	14	16	1.49	2.00	77.1	185	145	4	18	18	2.60	3.24
080	90.3	190	150	4	18	18	1.99	2.70	90.3	200	160	4	18	20	2.61	3.50
100	115.9	210	170	4	18	18	2.39	3.70	115.9	220	180	8	18	20	3.14	4.60
125	141.6	240	200	8	18	20	3.23	5.20	141.6	250	210	8	18	22	4.77	7.30
150	170.5	265	225	8	18	20	4.41	7.50	170.5	285	240	8	22	22	6.34	10.10
175	-	-	-	-	-	-	-	-	196.1	315	270	8	22	24	6.82	11.80
200	221.8	320	280	8	18	22	6.33	12.20	221.8	340	295	8	22	24	7.53	14.00
250	276.2	375	335	12	18	24	9.45	19.30	276.2	395	350	12	22	26	11.80	22.70
300	327.6	440	395	12	22	24	10.30	24.30	327.6	445	400	12	22	26	13.50	29.50
350	359.7	490	445	12	22	26	14.00	33.20	359.7	505	460	16	22	28	16.40	37.10
400	423.7	540	495	16	22	28	16.90	41.90	423.7	565	515	16	26	32	23.00	52.50
450	462.3	595	550	16	22	30	21.60	53.00	462.3	615	565	20	26	38	29.50	68.80
500	513.6	645	600	20	22	30	23.10	61.90	513.6	670	620	20	26	38	33.50	82.10


Slip-On

Series DIN 2576(PN16) PN16


Series DIN 2576(PN40) PN40

Blind

Series DIN 2527 PN16 & PN40




Slip-On Type



Blind Type

	DIN PN16								DIN PN40							
Size	d	D	C	no	h	t	Weight (kg)		d	D	C	no	h	t	Weight (kg)	
010	17.7	90	60	4	14	14	0.51	0.53	17.7	90	60	4	14	14	0.60	0.60
015	22.2	95	65	4	14	14	0.56	0.60	22.2	95	65	4	14	16	0.70	0.70
020	27.6	105	75	4	14	16	0.72	0.79	27.6	105	75	4	14	18	0.80	0.90
025	34.4	115	85	4	14	16	1.13	1.23	34.4	115	85	4	14	18	1.30	1.50
032	43.1	140	100	4	18	16	1.46	1.66	43.1	140	100	4	18	18	1.60	1.80
040	49	150	110	4	18	16	1.56	1.81	49	150	110	4	18	18	1.70	2.00
050	61.1	165	125	4	18	18	1.70	2.10	61.1	165	125	4	18	20	1.90	2.40
065	77.1	185	145	4	18	18	2.40	3.10	77.1	185	145	8	18	22	2.60	3.40
080	90.3	200	160	8	18	20	3.50	4.50	90.3	200	160	8	18	24	3.80	4.90
100	115.9	220	180	8	18	20	4.50	6.30	115.9	235	190	8	22	24	4.90	6.90
125	141.6	250	210	8	18	22	6.50	9.20	141.6	270	220	8	26	26	7.80	11.00
150	170.5	285	240	8	22	22	8.70	12.80	170.5	300	250	8	26	28	10.10	14.90
175	196.1	315	270	8	22	24	8.95	13.15	196.1	350	295	12	30	28	11.35	16.45
200	221.8	340	295	12	22	24	10.90	18.60	221.8	375	320	12	30	30	12.60	21.40
250	276.2	405	355	12	26	26	18.00	30.60	276.2	450	385	12	33	32	21.90	37.20
300	327.6	460	410	12	26	28	21.50	40.70	327.6	515	450	16	33	34	25.80	48.80
350	359.7	520	470	16	26	30	30.80	57.80	359.7	580	510	16	36	38	36.20	68.00
400	423.7	580	525	16	30	32	42.80	82.20	423.7	660	585	16	39	40	51.70	99.40
450	462.3	640	585	20	30	34	55.10	107.60	462.3	685	610	20	39	42	66.10	129.10
500	513.6	715	650	20	33	34	65.10	133.10	513.6	755	670	20	42	44	77.40	158.40


Series DIN 2633 ... PN16
Series DIN 2635 ... PN40



Weld-Neck

Size	DIN PN16								DIN PN40							
	d	D	C	No.	h	t	H-1	Weight KG	d	D	C	No.	h	t	H-1	Weight KG
010	17.2	90	60	4	14	14	35	0.58	17.2	90	60	4	14	16	35	0.66
015	21.3	95	65	4	14	14	35	0.65	21.3	95	65	4	14	16	38	0.75
020	26.9	105	75	4	14	16	38	0.95	26.9	105	75	4	14	18	40	1.06
025	33.7	115	85	4	14	16	38	1.14	33.7	115	85	4	14	18	40	1.29
032	42.4	140	100	4	18	16	40	1.69	42.4	140	100	4	18	18	42	1.88
040	48.3	150	110	4	18	16	42	1.86	48.3	150	110	4	18	18	45	2.33
050	60.3	165	125	4	18	18	45	2.53	60.3	165	125	4	18	20	48	2.82
065	76.1	185	145	4	18	18	45	3.06	76.1	185	145	8	18	22	52	3.74
080	88.9	200	160	8	18	20	50	3.7	88.9	200	160	8	18	24	58	4.75
100	114.3	220	180	8	18	20	52	4.62	114.3	235	190	8	22	24	65	6.52
125	139.7	250	210	8	18	22	55	6.3	139.7	270	220	8	26	26	68	9.07
150	168.3	285	240	8	22	22	55	7.75	168.3	300	250	8	26	28	75	11.8
175	193.7	315	270	8	22	24	60	9.85	193.7	350	295	12	30	32	82	18.2
200	219.1	340	295	12	22	24	62	11	219.1	375	320	12	30	34	88	21.5
250	273	405	355	12	26	26	70	15.6	273	450	385	12	33	38	105	34.9
300	323.9	460	410	12	26	28	78	22	323.9	515	450	16	33	42	115	49.7
350	355.6	520	470	16	26	30	82	31.2	355.6	580	510	16	33	46	125	68.1
400	406.4	580	525	16	30	32	85	39.3	406.4	660	585	16	39	50	135	96.5
500	508	715	650	20	33	34	90	61	508	755	670	20	42	52	140	117

Series DIN 86029 ... PN10
Series DIN 86030 ... PN16



Slip-On Raised Face

	DIN PN10								DIN PN16							
	Weight								Weight							
Size	d	D	C	No.	h	t	H-1	KG	d	D	C	No.	h	t	H-1	KG
010	17.7	90	60	4	14	14	20	0.56	17.7	90	60	4	14	14	20	0.56
015	22	95	65	4	14	14	20	0.64	22	95	65	4	14	14	20	0.64
020	27.6	105	75	4	14	16	24	0.98	27.6	105	75	4	14	16	24	0.98
025	34.4	115	85	4	14	16	24	1.12	34.4	115	85	4	14	16	24	1.12
032	43.1	140	100	4	18	16	26	1.58	43.1	140	100	4	18	16	26	1.58
040	49	150	110	4	18	16	26	1.77	49	150	110	4	18	16	26	1.77
050	61.1	165	125	4	18	18	28	2.40	61.1	165	125	4	18	18	28	2.40
065	77.1	185	145	4	18	18	32	3.10	77.1	185	145	4	18	18	32	3.10
080	90.3	200	160	8	18	20	34	3.80	90.3	200	160	8	18	20	34	3.80
100	115.9	220	180	8	18	20	38	4.30	115.9	220	180	8	18	20	38	4.30
125	141.6	250	210	8	18	22	40	5.80	141.6	250	210	8	18	22	40	5.80
150	170.5	285	240	8	22	22	44	7.10	170.5	285	240	8	22	22	44	7.10
175	196.1	315	270	8	22	24	44	9.10	196.1	315	270	8	22	24	44	9.10
200	222	340	295	8	22	24	44	9.90	222	340	295	12	22	24	44	9.70
250	276	395	350	12	22	26	46	12.70	276	405	355	12	26	26	46	13.40
300	327	445	400	12	22	26	46	14.40	327	460	410	12	26	28	46	17.30
350	359	505	460	16	22	26	53	22.30	359	520	470	16	26	30	57	27.60
400	410	565	515	16	26	26	57	26.70	410	580	525	16	30	32	63	36.00
500	512	670	620	20	26	28	67	37.30	512	715	650	20	33	34	73	56.40

1 Inch = 25.4mm

Inch	0	1/16	1/8	3/16	1/4	5/16	3/8	7/16	1/2	9/16	5/8	11/16	3/4	13/16	7/8	15/16
0	mm	1.6	3.2	4.8	6.4	7.9	9.5	11.1	12.7	14.3	15.9	17.5	19.1	20.6	22.2	23.8
1	25.4	27.0	28.6	30.2	31.8	33.3	34.9	36.5	38.1	39.7	41.3	42.9	44.5	46.0	47.6	49.2
2	50.8	52.4	54.0	55.6	57.2	58.7	60.3	61.9	63.5	65.1	66.7	68.3	69.9	71.4	73.0	74.6
3	76.2	77.8	79.4	81.0	82.6	84.1	85.7	87.3	88.9	90.5	92.1	93.7	95.3	96.8	98.4	100.0
4	101.6	103.2	104.8	106.4	108.0	109.5	111.1	112.7	114.3	115.9	117.5	119.1	120.7	122.2	123.8	125.4
5	127.0	128.6	130.2	131.8	133.4	134.9	136.5	138.1	139.7	141.3	142.9	144.5	146.1	147.6	149.2	150.8
6	152.4	154.0	155.6	157.2	158.8	160.3	161.9	163.5	165.1	166.7	168.3	169.9	171.5	173.0	174.6	176.2
7	177.8	179.4	181.0	182.6	184.2	185.7	187.3	188.9	190.5	192.1	193.7	195.3	196.9	198.4	200.0	201.6
8	203.2	204.8	206.4	208.0	209.6	211.1	212.7	214.3	215.9	217.5	219.1	220.7	222.3	223.8	225.4	227.0
9	228.6	230.2	231.8	233.4	235.0	236.5	238.1	239.7	241.3	242.9	244.5	246.1	247.7	249.2	250.8	252.4
10	254.0	255.6	257.2	258.8	260.4	261.9	263.5	265.1	266.7	268.3	269.9	271.5	273.1	274.6	276.2	277.8
11	279.4	281.0	282.6	284.2	285.8	287.3	288.9	290.5	292.1	293.7	295.3	296.9	298.5	300.0	301.6	303.2
12	304.8	306.4	308.0	309.6	311.2	312.7	314.3	315.9	317.5	319.1	320.7	322.3	323.9	325.4	327.0	328.6
13	330.2	331.8	333.4	335.0	336.6	338.1	339.7	341.3	342.9	344.5	346.1	347.7	349.3	350.8	352.4	354.0
14	355.6	357.2	358.8	360.4	362.0	363.5	365.1	366.7	368.3	369.9	371.5	373.1	374.7	376.2	377.8	379.4
15	381.0	382.6	384.2	385.8	387.4	388.9	390.5	392.1	393.7	395.3	396.9	398.5	400.1	401.6	403.2	404.8
16	406.4	408.0	409.6	411.2	412.8	414.3	415.9	417.5	419.1	420.7	422.3	423.9	425.5	427.0	428.6	430.2
17	431.8	433.4	435.0	436.6	438.2	439.7	441.3	442.9	444.5	446.1	447.7	449.3	450.9	452.4	454.0	455.6
18	457.2	458.8	460.4	462.0	463.6	465.1	466.7	468.3	469.9	471.5	473.1	474.7	476.3	477.8	479.4	481.0
19	482.6	484.2	485.8	487.4	489.0	490.5	492.1	493.7	495.3	496.9	498.5	500.1	501.7	503.2	504.8	506.4
20	508.0	509.6	511.2	512.8	514.4	515.9	517.5	519.1	520.7	522.3	523.9	525.5	527.1	528.6	530.2	531.8
21	533.4	535.0	536.6	538.2	539.8	541.3	542.9	544.5	546.1	547.7	549.3	550.9	552.5	554.0	555.6	557.2
22	558.8	560.4	562.0	563.6	565.2	566.7	568.3	569.9	571.5	573.1	574.7	576.3	577.9	579.4	581.0	582.6
23	584.2	585.8	587.4	589.0	590.6	592.1	593.7	595.3	596.9	598.5	600.1	601.7	603.3	604.8	606.4	608.0
24	609.6	611.2	612.8	614.4	616.0	617.5	619.1	620.7	622.3	623.9	625.5	627.1	628.7	630.2	631.8	633.4
25	635.0	636.6	638.2	639.8	641.4	642.9	644.5	646.1	647.7	649.3	650.9	652.5	654.1	655.6	657.2	658.8

Example:

In order to obtain the millimeter (mm) dimension for 7-1/2", find 7" on the x (vertical) axis and 1/2" on the y (horizontal) axis of the chart. The intersection of the two numbers is the millimeter (mm) equivalent to 7-1/2" (or 190.50mm).

Conversion Table - Pressure

From PSI to Kg/Cm2 and Kg/Cm2 to PSI

PSI	Kg/Cm2	PSI	Kg/Cm2	PSI	Kg/Cm2	PSI	Kg/Cm2	PSI	Kg/Cm2	PSI	Kg/Cm2	PSI	Kg/Cm2
1	0.07	31	2.18	61	4.29	91	6.40	205	14.42	410	28.83	710	49.93
2	0.14	32	2.25	62	4.36	92	6.47	210	14.77	420	29.54	720	50.63
3	0.21	33	2.32	63	4.43	93	6.54	215	15.12	430	30.24	730	51.34
4	0.28	34	2.39	64	4.50	94	6.61	220	15.47	440	30.94	740	52.04
5	0.35	35	2.46	65	4.57	95	6.68	225	15.82	450	31.65	750	52.74
6	0.42	36	2.53	66	4.64	96	6.75	230	16.17	460	32.35	760	53.45
7	0.49	37	2.60	67	4.71	97	6.82	235	16.53	470	33.05	770	54.15
8	0.56	38	2.67	68	4.78	98	6.89	240	16.88	480	33.76	780	54.85
9	0.63	39	2.74	69	4.85	99	6.96	245	17.23	490	34.46	790	55.56
10	0.70	40	2.81	70	4.92	100	7.03	250	17.58	500	35.16	800	56.26
11	0.77	41	2.88	71	4.99	105	7.38	255	17.93	510	35.86	810	56.96
12	0.84	42	2.95	72	5.06	110	7.74	260	18.28	520	36.57	820	57.67
13	0.91	43	3.02	73	5.13	115	8.09	265	18.64	530	37.27	830	58.37
14	0.98	44	3.09	74	5.20	120	8.44	270	18.99	540	37.97	840	59.07
15	1.05	45	3.16	75	5.27	125	8.79	275	19.34	550	38.68	850	59.77
16	1.13	46	3.23	76	5.34	130	9.14	280	19.69	560	39.38	860	60.48
17	1.20	47	3.31	77	5.41	135	9.49	285	20.04	570	40.08	870	61.18
18	1.27	48	3.38	78	5.49	140	9.85	290	20.39	580	40.79	880	61.88
19	1.34	49	3.45	79	5.56	145	10.20	295	20.75	590	41.49	890	62.59
20	1.41	50	3.52	80	5.63	150	10.55	300	21.10	600	42.19	900	63.29
21	1.48	51	3.59	81	5.70	155	10.90	310	21.80	610	42.90	910	63.99
22	1.55	52	3.66	82	5.77	160	11.25	320	22.50	620	43.60	920	64.70
23	1.62	53	3.73	83	5.84	165	11.60	330	23.21	630	44.30	930	65.40
24	1.69	54	3.80	84	5.91	170	11.95	340	23.91	640	45.01	940	66.10
25	1.76	55	3.87	85	5.98	175	12.31	350	24.61	650	45.71	950	66.81
26	1.83	56	3.94	86	6.05	180	12.66	360	25.32	660	46.41	960	67.51
27	1.90	57	4.01	87	6.12	185	13.01	370	26.02	670	47.12	970	68.21
28	1.97	58	4.08	88	6.19	190	13.36	380	26.72	680	47.82	980	68.92
29	2.04	59	4.15	89	6.26	195	13.71	390	27.43	690	48.52	990	69.62
30	2.11	60	4.22	90	6.33	200	14.06	400	28.13	700	49.23	1000	70.32
												1500	105.49

To convert to Kg/Cm2 from PSI, divide PSI by 14.22

To convert to PSI from Kg/Cm2, multiply Kg/Cm2 by 14.22

Conversion Table - Temperature

From Fahrenheit to Celsius and Celsius to Fahrenheit

F	C	F	C	F	C	F	C	F	C	F	C
-160	-106.7	-40	-40.0	75	23.9	195	90.6	850	454.4	2050	1121.1
-155	-103.9	-35	-37.2	80	26.7	200	93.3	900	482.2	2100	1148.9
-150	-101.1	-30	-34.4	85	29.4	205	96.1	950	510.0	2150	1176.7
-145	-98.3	-25	-31.7	90	32.2	210	98.9	1000	537.8	2200	1204.4
-140	-95.6	-20	-28.9	95	35.0	212	100.0	1050	565.6	2250	1232.2
-135	-92.8	-15	-26.1	100	37.8	215	101.7	1100	593.3	2300	1260.0
-130	-90.0	-10	-23.3	105	40.6	220	104.4	1150	621.1	2350	1287.8
-125	-87.2	-5	-20.6	110	43.3	225	107.2	1200	648.9	2400	1315.6
-120	-84.4	0	-17.8	115	46.1	230	110.0	1250	676.7	2450	1343.3
-115	-81.7	5	-15.0	120	48.9	235	112.8	1300	704.4	2500	1371.1
-110	-78.9	10	-12.2	125	51.7	240	115.6	1350	732.2	2550	1398.9
-105	-76.1	15	-9.4	130	54.4	245	118.3	1400	760.0	2600	1426.7
-100	-73.3	20	-6.7	135	57.2	250	121.1	1450	787.8	2650	1454.4
-95	-70.6	25	-3.9	140	60.0	300	148.9	1500	815.6	2700	1482.2
-90	-67.8	30	-1.1	145	62.8	350	176.7	1550	843.3	2750	1510.0
-85	-65.0	32	0.0	150	65.6	400	204.4	1600	871.1	2800	1537.8
-80	-62.2	35	1.7	155	68.3	450	232.2	1650	898.9	2850	1565.6
-75	-59.4	40	4.4	160	71.1	500	260.0	1700	926.7	2900	1593.3
-70	-56.7	45	7.2	165	73.9	550	287.8	1750	954.4	2950	1621.1
-65	-53.9	50	10.0	170	76.7	600	315.6	1800	982.2	3000	1648.9
-60	-51.1	55	12.8	175	79.4	650	343.3	1850	1010.0	3050	1676.7
-55	-48.3	60	15.6	180	82.2	700	371.1	1900	1037.8	3100	1704.4
-50	-45.6	65	18.3	185	85.0	750	398.9	1950	1065.6	3150	1732.2
-45	-42.8	70	21.1	190	87.8	800	426.7	2000	1093.3	3200	1760.0

To convert to Fahrenheit from Celsius: $F = 32 + 9/5 C$

To convert to Celsius from Fahrenheit: $C = 5/9 (F-32)$